

Product	Kg/ltr	Flash Point	Product Description
GMA130	N/A	N/A	Non-slip aggregate for deck systems.
GMA131	N/A	N/A	Non-slip aggregate for deck systems.
GMA132	N/A	N/A	Non-slip aggregate for deck systems.
GMA197	N/A	N/A	Non-slip aggregate for deck systems.
GMA904	N/A	N/A	Conventional paint and varnish remover.
GTA004	0.78	38°C	A thinner and equipment cleaner for use with Interclene, Interlac, Interprime and some one pack Intertuf products.
GTA007	0.86	26°C	A thinner and equipment cleaner for use with Interchlor, Interclene, Interfine, Interprime, Intersheen, Intersleek, Intersmooth, Interspeed, Interswift, Intertherm and certain one pack Intertuf products as well as Intershield epoxy non-skid deck coatings.
GTA056	0.81	39°C	A thinner and equipment cleaner for use with certain Intershield and Interthane polyurethane products in North America.
GTA065	0.91	31°C	A reactive thinner for use with certain polyester systems.
GTA075	0.84	3°C	A thinner for use with certain epoxy shop (pre-construction) primers in South America.
GTA137	0.83	1°C	A thinner and equipment cleaner for use with certain epoxy/urethane primers and polyurethane finishes in South America.
GTA138	0.92	32°C	A thinner and equipment cleaner for use with certain Interzinc zinc silicate products.
GTA220	0.85	25°C	A thinner and equipment cleaner for use with Interbond, Intergard, Interline and Intershield products as well as Intertuf coal tar epoxy and Interzinc zinc epoxy coatings.
GTA313	0.94	34°C	An acetate/ketone blend primarily used with polyurethane finishes.
GTA407	0.85	19°C	A thinner and equipment cleaner for use with vinyl antifoulings in North America.
GTA415	0.88	25°C	A thinner and/or equipment cleaner for use with certain Intergard and Interline epoxy coatings and with certain Interplate and Interzinc products.
GTA420	0.86	20°C	A thinner for use with Interline 850.
GTA713	0.91	30°C	A thinner and equipment cleaner for use with Interthane polyurethane and Intertuf pitch urethane products.
GTA803	0.82	-17°C	A thinner and equipment cleaner for use with certain Interplate and Interzinc products.
GTA820	0.82	5°C	A thinner and equipment cleaner for use with certain Interplate products (for use in warmer conditions).
GTA822	0.85	26°C	An equipment cleaner for use with Interbond, Intergard, Interline and Intershield epoxy coatings as well as certain Intertuf coal tar epoxy and Intersleek products.
GTA840	0.83	17°C	A thinner and equipment cleaner for use with certain Interplate products (for use in cooler conditions).
GTA853	0.82	15°C	A thinner and equipment cleaner for use with Intertuf 23.
Non Slip Aggregate	N/A	N/A	Non-slip aggregate for deck systems.
5822	0.84	32°C	A thinner and equipment cleaner for use with certain Epoxy MIL-SPEC products in North America.
7754D	N/A	N/A	A non-slip aggregate for Interzone 1000 systems.

**REGULATORY
DATA**

The EPA has defined almost all solvents, including all those contained herein, as photochemically active. The exceptions include methanol, ethanol, acetone and a few halogenated solvents such as methylene chloride.

SAFETY

All work involving the application and use of this product should be performed in compliance with all relevant national Health, Safety & Environmental standards and regulations. Prior to use, obtain, consult and follow the Material Safety Data Sheet for this product concerning health and safety information. Read and follow all precautionary notices on the Material Safety Data Sheet and container labels. If you do not fully understand these warnings and instructions or if you can not strictly comply with them, do not use this product. Proper ventilation and protective measures must be provided during application and drying to keep solvent vapour concentrations within safe limits and to protect against toxic or oxygen deficient hazards. Take precautions to avoid skin and eye contact (ie. gloves, goggles, face masks, barrier creams etc.) Actual safety measures are dependant on application methods and work environment.

EMERGENCY CONTACT NUMBERS:

USA/Canada - Medical Advisory Number 1-800-854-6813

Europe - Contact (44) 191 4696111. For advice to Doctors & Hospitals only contact (44) 207 6359191


R.O.W. - Contact Regional Office

LIMITATIONS

For supply in USA the **International - USA** datasheet should be used.
Flashpoint and SG may vary slightly from the figures quoted above due to locally sourced solvents.

IMPORTANT NOTE

The information in this data sheet is not intended to be exhaustive: any person using the product for any purpose other than that specifically recommended in this data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at their own risk. All advice given or statements made about the product (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability at all for the performance of the product or for (subject to law) any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our Conditions of Sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to check with their local International Paint representative that this data sheet is current prior to using the product.

 and product names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

© Akzo Nobel 2004

Worldwide Operations

Argentina, Australia, Bahrain, Belgium, Brazil, Bulgaria, Canada, Chile, Colombia, Croatia, Cuba, Cyprus, Denmark, Ecuador, Egypt, Estonia, Fiji, Finland, France, Germany, Greece, Hong Kong, Iceland, India, Indonesia, Iran, Italy, Japan, Kuwait, Latvia, Lithuania, Luxembourg, Malaysia, Malta, Mexico, Netherlands, New Zealand, Northern Ireland, Norway, Pakistan, Panama, Papua New Guinea, Peoples Republic of China, Peru, Philippines, Poland, Portugal, Qatar, Republic of Ireland, Romania, Russia, Saudi Arabia, Singapore, Slovenia, South Africa, South Korea, Spain, Sri Lanka, Sweden, Taiwan, Thailand, Turkey, U.S.A., Ukraine, United Arab Emirates, United Kingdom, Uruguay, Venezuela, Vietnam, Western Samoa, Yemen

Head Office

International Paint Ltd, Oriol House, 16 Connaught Place, London W2 2ZB, United Kingdom, Tel: +44 (0) 207 479 6000, Fax: +44 (0) 207 479 6500

www.international-marine.com